

# Data sheet

sw-410.556

ESD Euro system dolly with 2 load surfaces (edge 10 mm)



**External dimensions:**

|         |        |                |  |
|---------|--------|----------------|--|
| Width:  | 675 mm | Construction:  | steel, screwed                             |
| Depth:  | 415 mm | Colour:        | RAL 7024 graphite grey / powder-coated ESD |
| Height: | 665 mm | Weight:        | 20 kg                                      |
|         |        | Load capacity: | 250 kg                                     |

**Loading surface: (w/d)**

|                         |  |        |  |
|-------------------------|--|--------|--|
| Material:               | decor chipboard / ESD covering / RAL 7035 light grey |        |  |
| Bottom:                 | 605 mm x 410 mm                                      |        |  |
| Shelf:                  | 605 mm x 410 mm                                      |        |  |
| Loading height:         | 225 mm   | 655 mm |  |
| Clearance height:       | 410 mm   |        |  |
| Height of frame:        | 10 mm  |        |  |
| Load capacity of shelf: | 80 kg  |        |  |

|                  |  |
|------------------|--|
| <b>Wheelset:</b> | Ø 125 x 32 mm, electrically conductive thermoplastic rubber, non-marking |
|                  | 4 swivel castors   |
|                  | deepgroove ball bearings   |
|                  | EasySTOP accessible from one side  |
|                  | More safety with the VARIOfit® foot protection                           |

|                    |                    |
|--------------------|--------------------|
| EAN-No.            | 4035694041103      |
| Customs tariff no. | 87168000           |
| Country of origin: | European Community |

