

# Data sheet



sw-600.614

Order picking trolley with 3 shelves, low



12  
years  
warranty

**Outer dimensions:**

Width: 1455 mm  
Depth: 625 mm  
Height: 1320 mm  
Weight: 40 kg

**Inner dimensions:**

Width: 985 mm  
Depth: 605 mm

Construction: steel, fixed welded  
Colour: RAL 5010 gentian blue / powder-coated  
Load capacity: 250 kg

Order picking trolley with 3 shelves, low  
Outer dimensions: 1,455 x 625 x 1,320 mm (W/D/H)  
Loading surface of bottom: 985 x 605 mm (W/D)  
Loading surface of shelf: 985 x 590 mm (W/D)  
Loading heights: 185 / 805 mm  
Useful distance between shelves: 590 mm  
Created by:

\* 2 step treads of waterproof bonded plywood at the front; Step treads lift automatically in the unloaded condition via a gas spring strut; In the loaded condition the step treads lower to the ground; Step treads can be folded in rest position

\* Height of top step: 500 mm

\* Step height: 230 mm

\* safety bar for holding and leaning

\* load surface and shelves inserted in angle steel frame, edge 15 mm high

\* load surface and shelves of wood-based board, surface finish beech; Load capacity upper and middle shelf: 80 kg

Colour: gentian blue RAL 5010, powder coated

Wheelset:

125 mm grey non-marking thermoplastic rubber tyres on plastic wheel rim with precision deepgroove ball bearings; Thread guard and foot guard; 2 swivel castors with brakes and 2 fixed castor  
Load capacity: 250 kg

**Wheelset:**

Ø 125 x 32 mm, thermoplastic rubber, grey, non-marking  
2 swivel castors with brakes and 2 fixed castors  
deepgroove ball bearings  
More safety with the VARIOfit® foot protection

Customs tariff no: 87168000

Country of origin: European Community

[www.VARIOfit.eu](http://www.VARIOfit.eu)

